

---

# Electromethanogenesis pilot

Geoffrey Karakachian, ENGIE

lab CRIGEN

Thessaloniki

20/06/2024



Co-funded by  
the European Union

innovations in the  
**BIOMETHA**<sup>ne</sup>  
uni**VERSE**

# Demo Site in France

## Demonstration site: EVRON , MAYENNE

**Feedstock:** 30 000t/y (70% agro-industrial residues +30% agricultural residues)


**Type :** Continuously Stirred Tank Reactor // Mesophilic // Upgrading via membrane

The unit injected its first m<sup>3</sup> of biomethane in November 2021

Several solid and liquid feed lanes, adapted to the type of input.


### Main numbers:

- **21 GWh /y** of biomethane production
- **Up to 220Nm<sup>3</sup>/h** injected into NG grid
- **9 000 m<sup>3</sup>** digestion volume ( HRT> 50 d ) :
  - 2 Main digesters of 4 500 m<sup>3</sup>
- **21,000 m<sup>3</sup>** of liquid digestate storage
- **1 800 m<sup>3</sup>** of solid digestate storage
  - Valorization of digestate by land spreading
- **(3 000 ha, 21 farms).**




# Technology description

## 1 chamber reactor : Boost of biogas production rate



## 2 chamber reactor : Biogas upgrading towards high $CH_4$ %



- Electromethanogenesis is at the **frontier between electrolysis** ( $H_2$  production in-situ) **and biological methanation** ( $H_2 + CO_2$  conversion into  $CH_4$ ).
- The technology relies on the use of **electrodes inserted into digestate or given medium**. Under voltage, the micro-organism activity within the biofilm attached to the electrodes is boosted and leads to higher biogas production and/or quality.
- Fine tuning of electrochemistry and biochemistry favorize the production of  $CH_4$ .
- Technology aiming at increasing the biomethane production of AD unit and gas quality.



# Ambition and progress beyond the state of the art

**Ambition :** Increase biomethane production on the AD unit **using the effluent digestate, biogas of the main digester and external green electricity** from solar and wind.


TRL Objective : 4 → 6/7

## Single chamber reactor (1c-AD-BES)

- Electrodes directly immersed in the digestate.
- **Planned pilot is a reactor of 1 m<sup>3</sup>** reactor working at the same mesophilic temperature of the main AD plant.
- **Electrical power source < 2 V** driven by a renewable energy mix from local wind and photovoltaic electricity generators.
- **Enhancement of the bioelectrode geometry and electron transfer properties by prior surface treatment**
- Coupling the 1c-AD-BES downstream the main digester, the **aim is to have a surplus production of 100 L-CH<sub>4</sub>/m<sup>3</sup>/d to the already existing production.**

## Double chamber reactor (2c-AD-BES)

- Electrodes separated by a membrane, water oxidation (anodic part) and CO<sub>2</sub> (-biogas) reduction (cathodic part).
- **Planned pilot is a reactor of 1 m<sup>3</sup>**
- Injection of **biogas (from the main digester first and then from 1c-AD-BES reactor)**, enabling an efficient power-to-gas process in a H<sub>2</sub>O/CO<sub>2</sub> electrosynthesis cell
- **2c-AD-BES is an upgrading step towards maximum biomethane purity output.** At lab scale, the **current two-chamber system can produce 200-1000 L CH<sub>4</sub> per day per m<sup>3</sup> reactor volume**



INPUT	OUTPUT
Digestate 230 L/d	Biomethane 200 L (95% CH <sub>4</sub> + 5% CO <sub>2</sub> )
Electrical power (balance of plant) 13,2 kW (64.5 kWh/d)	Thermal energy 1.7kWh/d
Electrical power (electrodes) 3-160 W (0.072- 3.84 kWh/d)	



# Challenges

## Performances challenges :

Previous lab experiences showed that **two main parameters contribute to increase biogas/biomethane production in AD-BES:**



- Available surface for biofilm growth, due to electrodes presence
- Application of an optimal voltage for the stimulation of electro-active microbes.
  - **Labscale trials (2023) : (LEITAT-DTU-FAU)**
    1. Pretreatment of electrode materials → maximizing the bioelectrochemical performances
    2. Pretreatment of the substrate (AD digestate) → facilitating the substrate degradation

## Operational challenges :

- Feeding conditions at upscaled level : continuous feeding investigation
- Inoculation of anode and cathode with proper electro-active biofilms
  - **Pre-pilot testing at 10/15 L scale (2023-2024) (LEITAT-DTU)**

## Safety challenges :

- Safe usage of the pilot on an operational demo-site
  - SAFETY Studies (ENGIE-AERIS) :
    - **HAZID study (Sept. 2023) :**  
Hazard identification considering the pilot in its environment
    - **ATEX study (2023) :**  
Identification of the ATEX zoning of the pilot and setting-up of mitigation measure → input for the future pilot localisation
    - **HAZOP study (Jan. 2024) :**  
Operational hazard identification on the pilot usage



# Digestate characterization and pretreatment

Sieving



Figure 1 – Sieved post-digestate with 2 mm mesh (Source: Leitatz)

Grinding



Figure 2 – Grinded post-digestate for 1 min at 1500 rpm (Source: Leitatz)

2 approaches were investigated at LEITAT :

- Sieving (gave the best results)
- Grinding



Liquid digestate produced at AD site was sent and used for characterization and lab scale work.

Parameter	Post-digester (2023)	Sieving	Liquid digestate
pH (-)	8,17±0,04	8,86±0,06	8,39±0,01
Cond. (mS/cm)	16,51±0,16	13,02±0,01	29,2±0,08
COD <sub>tot</sub> (g/L)	79,33±3,09	64,07±0,61	61,03±0,82
COD <sub>sol</sub> (g/L)	45,37±0,56	31,67±0,31	33±8,31
COD <sub>sol</sub> /COD <sub>tot</sub> (%)	57,26%	49,44%	53,90%
BOD <sub>5,tot</sub> (g/L)	10,482±1,05	8,546±0,23	5,644±0,116
BOD <sub>5,sol</sub> (g/L)	2,1±0,21	2,21±0,15	2,15±0,394
TN (g/L)	6,51±0,21	3,62±0,17	8,18±0,89
TAN (g/L)	2,98±0,03	0,93±0	5,03±0,12
Nitrates (NO <sub>3</sub> <sup>-</sup> N g/L)	0,319±0,02	0,288±0,039	0,242±0,004
COD <sub>sol</sub> /TN ratio (-)	6,98±0,29	8,76±0,47	7,55±0,83
PO <sub>4</sub> <sup>3-</sup> -P (g/L)	0,573±0,01	0,505±0,01	0,49±0,01
K (g/L)	3,52±0,03	3,61±0,24	4,13±0,12
TS (g/L)	92,1±0,6	99,3±1,6	89,8±0,4
VS (g/L)	64,6±0,7	66,4±1,1	47,1±3,3
Alkalinity (mg/L)	4,436±0,255	5,248±0,056	4,569±0,086
FOS/TAC	0,249±0,02	0,479±0,01	0,192±0
Viscosity (Pa s)	8,39±0,63	3,89±0,64	0,84±0,07

Conclusions : Solid part in the digestate might cause operative issue → **Decision to go for liquid digestate directly produced at demo site**




# Lab-scale trials on EMG for 1c AD-BES




- The PT should only be applied to anodes as cathodes do not improve when inoculated with Th-PT
- Higher biogas qualities are obtained for 0,3 V
- OPS stabilize biogas production among cycles
- No clear difference between the voltages applied is observed

→ No electrode pretreatment will be applied for the pilot

For an applied voltage of 0,3 V



For an applied voltage of 0,7 V



# Reactor engineering, pre-pilot scale (M4-M27)



## Reactors:

- AD useful volume: 10 L
- AD-BES useful volume: 9,57 L

## Electrodes:

- 3 cathodes and 2 anodes → ratio CAT/AN 3
- $S/V = 13 \text{ m}^2/\text{m}^3$

Parameters	Periodicity
pH, electrode potentials	Twice per week
Temperature, voltage, current density	Continuous
Gas production rate	Once per day
Gas composition, COD, FOS/TAC, TS, VS, $\text{NH}_4^+$	Once per week
Organic acid profile	Once per phase



## Plan of experiments:

- 8 weeks inoculation + 4 weeks operation
- 4 weeks of voltage testing
- 4 weeks of intermittent voltage testing
- 12 weeks of HRT testing
- XX weeks of organic overloading testing





# Double chamber reactor (2c-ADBES) : voltage optimization

## Different Voltage to supply the water splitting

High voltage supplies a higher amount of H<sub>2</sub>, which supports a higher biogas treatment ability.

Multi layer cathode Single layer cathode


Power supply

pH Control

Raw biogas


60% CH<sub>4</sub>,  
40%

Water bath



Upgraded biogas

In optimized conditions the 2C-ADBES is able to upgrade biogas to biomethane specification in terms of CH<sub>4</sub> content




Optimized voltage for the size tested

Further biogas upgrading capability with higher voltage

# Double chamber reactor (2c-ADBES) : pre-pilot system preparation

Feasibility verification pre-pilot using 20 L reactor,  
Feed **pure CO<sub>2</sub>** with different feed speeds, Voltage: 4V



- Pre-pilot reactor worked with anaerobic granular sludge, higher than 70% CO<sub>2</sub> was converted to CH<sub>4</sub>, with a feed speed of 151 L/m<sup>3</sup><sub>reactor</sub>/day at 4 V.

Next steps:

- feed with **biogas**,
- **optimize** working parameters
- **increase feedrate** (target at 1000 L/(m<sup>3</sup>\*d))

# CFD simulations - 1c-AD-BES prepilot

## CFD Simulations

➤ Uses numerical analysis to give insights into fluid flows




Simulation results already provide information about

- Flow pattern
- Mixing in the reactor
- Microscale of turbulence (Kolmogorov length), a parameter that allows estimation of possible damage to particulate components
- Turbulent kinetic energy
- Power input into the reactor


Simulation results will be provide information about

- Load variables (shear stress)
- Residence time distribution
- Bubble size distribution (gas-liquid systems)
- Bubble residence time prediction (gas-liquid systems)
- Reactions
- ...

We can run multiple simulations and compare different setups and configurations



AD



AD-BES 1

Steady state simulations  
Turbulence model: k-epsilon model  
Rotational speed: 300 rpm  
Material data of water but with a higher viscosity of 840 mPas





# CFD simulations - 1c-AD-BES pilot


## Comparison of operation with and without recirculation

With recirculation

Without recirculation



# Initial Business perspective



Scenario	AD reference case	+ 40% CH <sub>4</sub> production
CH <sub>4</sub> – Nm <sup>3</sup> /h	250	350
CAPEX – k€	9,044	11,886
OPEX – k€/y	1,038	1,170
LCOE - €/MWh-HHV	87	71 (- 18%)

From first assessment of the technology with lab-scale data, a **+40% CH<sub>4</sub> production using EMG could lead to LCOE reduction of about 18%**

• **Policy** : discussion ongoing with (Direction Regional de l'Environnement et de l'Aménagement et du Logement) : regulatory body in France.

- **Actions** : realizing a legal document called (*Porté à connaissance*) → public document aiming at showing the full safety of a given installation (in here the EMG pilot) for people and goods. → integration of safety study outcomes (HAZID/HAZOP)
  - This action will help EMG to be recognized by as an innovative technology by regional decision makers ( mayors, préfets...) and could favorize technology acceptance and development

➤ **Methodological analysis of the pilot :**

- Costs (OPEX & CAPEX)
- Operation (safety, usage, digestate quality)
- Performances (biogas & biomethane production)
  - Pre-pilot and full-pilot scale for challenging the first economical perspectives
- Mass and energy balance
- Bill of material

Data provision all along the project for :

- **WP3 Assessment and Optimisation** : *assessment of the demonstrators as built within the project, and of their potential optimised and upscaled configurations*
- **WP4 Replicability** : *assessment of the replicability potential of technology pathways adopted and tested by demonstrators.*



Towards market penetration and stakeholder acceptance



#Biomethaverse

# Thank you!

## Follow Biomethaverse:

[www.biomethaverse.eu](http://www.biomethaverse.eu) 

[@European\\_Biogas](https://twitter.com/European_Biogas) 

[@European Biogas Association](https://www.linkedin.com/company/european-biogas-association/) 

Contact: **Geoffrey Karakachian**

Email: **[geoffrey.karakachian@engie.com](mailto:geoffrey.karakachian@engie.com)**

*Co-funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or CINEA. Neither the European Union nor the granting authority can be held responsible for them.*



Co-funded by  
the European Union